

Project · Reference number


Date

Product data sheet

Application

Luminaire for installation on pillars, walls and parapets.
A luminaire with antique glass for brilliant light.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
BEGA Unidure® coating technology
Antique glass
Mounting plate with 3 fixing holes \varnothing 5.5 mm
Angle 120° · Pitch circle \varnothing 85 mm
Mounting bracket with 2-pole terminal block 4[□] and earth conductor terminal for connection of mains supply cable max. $3 \times 2.5^{\square}$
Lampholder E 27
Safety class I
Protection class IP 23
Protected against granular foreign bodies ≥ 12 mm and showers up to 60°
 – Safety mark
CE – Conformity mark
Weight: 3.2 kg

Lamp

Luminaire with screw base E 27
Lamp output max. 100 W
This product contains light source of energy efficiency class E

Supplied lamp
BEGA LED lamp **13 590**
LED Retrofit 12 W · 1400 lm · 3000 K

Luminaire efficiency: 46.4%

Additional BEGA LED lamps are available for this luminaire:

- 13 584** LED 7 W · 805 lm · 3000 K
- 13 586** LED 7 W · 805 lm · 3000 K
dimmmable
- 13 588** LED 8 W · 1055 lm · 3000 K
- 13 592** LED 12 W · 1400 lm · 3000 K
dimmmable

Radio-controlled version (Zigbee 3.0):

- 13 555** LED 9 W · 805 lm · 2700 K
dimmmable
- 13 556** LED 9 W · 805 lm · 2700-6500 K
dimmmable · tunable white
- 13 557** LED 9.5 W · 805 lm · 2700-6500 K
dimmmable · tunable white · RGBW

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

