

BEGA**31 435**

Wall luminaire »Brügge«



Project · Reference number

Date


Product data sheet

Application

Wall luminaire for many lighting tasks on or in buildings.

A luminaire with antique glass diffuser for brilliant light.

Product description

Luminaire made of aluminium alloy,
aluminium and stainless steel
BEGA Unidure® coating technology
Antique glass
Wall mounting with a mounting plate made of
stainless steel, Steel grade number 1.4301
Mounting plate with 2 fixing
holes \varnothing 5 mm · 70 mm spacing
1 cable entry for mains supply cable
up to \varnothing 10,5 mm
Connecting terminals 2.5[□]
Earth conductor connection
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies
 \geq 1 mm and splash water
Impact strength IK02
Protection against mechanical
impacts < 0.2 joule
 – Safety mark
CE – Conformity mark
Weight: 2.2 kg

Lamp

Luminaire with screw base E 27
Lamp output max. 60 W
This product contains light source of energy
efficiency class E

Supplied lamp

BEGA LED lamp **13584**
LED Retrofit 7 W · 805 lm · 3000 K

Luminaire efficiency: 46%

Additional BEGA LED lamps are available for
this luminaire:

- 13586** LED 7 W · 805 lm · 3000 K
dimnable
- 13588** LED 8 W · 1055 lm · 3000 K
- 13590** LED 12 W · 1400 lm · 3000 K
- 13592** LED 12 W · 1400 lm · 3000 K
dimnable

Radio-controlled version (Zigbee 3.0):

- 13555** LED 9 W · 805 lm · 2700 K
dimnable
- 13556** LED 9 W · 805 lm · 2700-6500 K
dimnable · tunable white
- 13557** LED 9.5 W · 805 lm · 2700-6500 K
dimnable · tunable white · RGBW

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.

