

BEGA**31 559**

Pillar luminaire »Brügge«



Project · Reference number

Date

Product data sheet

Application

Luminaire for installation on pillars, walls or parapets for interior and exterior applications.
Luminaire with hand-blown crystal bubble glass for brilliant light.

Product description

Luminaire made of aluminium alloy,
aluminium and stainless steel
BEGA Unidure® coating technology
Crystal bubble glass
Mounting plate with 3 fixing holes \varnothing 8.5 mm
Angle 120° · Pitch circle \varnothing 100 mm
Mounting bracket with 2-pole terminal block 4[□]
and earth conductor terminal for connection of
mains supply cable max. 3 × 2.5[□]
Lampholder E 27
Safety class I
Protection class IP 44
Protected against granular foreign bodies
≥ 1 mm and splash water
Impact strength IK02
Protection against mechanical
impacts < 0.2 joule
 – Safety mark
CE – Conformity mark
Weight: 4.6 kg

Lamp

Luminaire with screw base E 27
Lamp output max. 100 W
This product contains light source of energy
efficiency class E

Supplied lamp

BEGA LED lamp **13584**
LED Retrofit 7 W · 805 lm · 3000 K

Luminaire efficiency: 59%

Additional BEGA LED lamps are available for
this luminaire:

- 13586** LED 7 W · 805 lm · 3000 K
dimmable
- 13588** LED 8 W · 1055 lm · 3000 K
- 13590** LED 12 W · 1400 lm · 3000 K
- 13592** LED 12 W · 1400 lm · 3000 K
dimmable

Detailed technical and lighting data for the
lamps can be found in the data sheets on our
website.

