BEGA 31 019

Wall luminaire

Project · Reference number Date

Product data sheet

Application

Wall luminaire with cylindrical lens for concentrated and directed light. For interior and exterior applications. Luminaire distinguished by its high corrosion resistance.

Product description

Luminaire made of copper, brass and stainless steel Optical cylindrical lens made of crystal glass Mounting plate with 2 fixing holes ø 5.5 mm · 70 mm spacing 1 cable entry for mains supply cable up to ø 10,5 mm Connecting terminal 2.5⁻¹ with plug connection Earth conductor connection Lampholder E 27 Safety class I Protection class IP 44 Protected against granular foreign bodies ≥ 1 mm and splash water Impact strength IK05 Protection against mechanical impacts < 0.7 joule **₹10** 🏝 – Safety mark C € – Conformity mark Weight: 2.6 kg

Lighting technology

Luminaire data for the DIALux lighting design program for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at www.bega.com.

Lamp

Luminaire with screw base E 27 Lamp output max. 100 W This product contains light source of energy efficiency class E

Supplied lamp BEGA LED lamp **13590** LED Retrofit 12 W · 1400 lm · 3000 K

Luminaire efficiency: 60%

Additional BEGA LED lamps are available for this luminaire:

13584 LED 7 W · 805 lm · 3000 K 13586 LED 7 W · 805 lm · 3000 K dimmable 13588 LED 8 W · 1055 lm · 3000 K 13592 LED 12 W · 1400 lm · 3000 K dimmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.





Copper

The luminaire parts made of solid copper are delivered with the metal's natural surface colour. Time and weather factors create the natural patina characteristic for copper.