

BEGA**71 070**

Connecting Pillar

IP 44

Project · Reference number

Date

Product data sheet**Application**

Permanent connecting pillar for private use.
For the connection of electrically driven gardening tools or portable garden luminaires.

Product description

Connecting pillar made of aluminium alloy,
aluminium and stainless steel
BEGA Unidure® coating technology
Support and cover GRP
Colour graphite
Connecting pillar with mounting base
made of hot-dip galvanised steel according
to EN ISO 1461 for bolting onto a foundation
provided by the customer or on other paved
surfaces such as terraces and paving stones
Base plate with 3 fixing holes
ø 5.5 mm · Pitch 120° · Pitch circle ø 60 mm
3 Safety socket outlets 16A · 250V ~
Plug type E: system common in France and
Belgium
Suitable for electrical load pursuant to
DIN VDE 0620-2-1 with safety plug in
accordance with DIN 49441 or DIN 49406
Line connector for mains supply cable
ø 8-14 mm, max. 5 × 2,5[□]
Safety class I
Protection class IP 44
Protected against granular foreign bodies
≥ 1 mm and splash water
(with closed flap)
CE – Conformity mark
Weight: 2.4 kg

Accessories

70 730 Distribution box for installation in soil
with 7 cable entries
Connection terminals 5 × 4[□]

A separate instructions for use can be provided
upon request.

